



Fums Bearing CO.,LTD



SKF NTN NSK NMB Koyo NACHI Timken
Deep Groove Ball Bearing 16006 16007 16008
16009 16010

Bearing No. 16006

16006 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 30x55x9 mm |
| Bore Diameter | 30 mm |
| Outer Diameter | 55 mm |
| Width | 9 mm |
| d | 30 mm |
| D | 55 mm |
| B | 9 mm |
| C | 9 mm |
| r min. | 0.3 mm |
| da min. | 35 mm |
| Da max. | 50 mm |
| ra max. | 0.3 mm |
| Weight | 0.085 Kg |
| Basic dynamic load rating (C) | 9,95 kN |
| Basic static load rating (C0) | 6,55 kN |
| (Grease) Lubrication Speed | 12000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |



Fums Bearing CO.,LTD

| | |
|---------------------------------|--|
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 30MM Bore; 55MM Outside Diameter; 9MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Weight / LBS | 0.2072 |
| Outer Race Width | 0.354 Inch 9 Millimeter |
| Bore | 1.181 Inch 30 Millimeter |
| Outside Diameter | 2.165 Inch 55 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 30 mm |
| Width | 9 mm |
| Fillet Radius/Chamfer | 0.3 mm |
| | |



Fums Bearing CO.,LTD

| | |
|-------------------------|-------------------|
| Dynamic Load Rating | 9,950 N |
| Static Load Rating | 6,550 N |
| Limiting Speed - Grease | 13,000 rpm |
| Limiting Speed - Oil | 15,000 rpm |
| Factor fo | 15.4 |
| Radial Clearance | 0.005 to 0.020 mm |
| da (min) | 35 mm |
| Da (max) | 50 mm |
| ra (max) | 0.3 mm |